

EF 400mm f/4 DO IS II USM		
Optical Features/Specifications		
	Angle of view (horzntl, vertl, diagonl)	5°10', 3°30', 6°10'
	Lens construction (elements/groups)	18/12
	No. of diaphragm blades	9
	Minimum aperture	32
	Closest focussing distance (m)	3.3
	Maximum magnification (x)	0.13
	Distance Information	Yes
	Image stabilizer	4 stops
	AF actuator	Ring USM ³
Physical Specifications		
	Dust/moisture resistance ⁴	Yes
	Filter diameter (mm)	52 Drop in
	Max. diameter x length (mm)	128 x 232.7
	Weight (g)	2100
Accessories		
	Lens cap	E-145C
	Lens hood	ET-120 (WII)
	Lens case/pouch	Lens Case 400D
	Rear cap	Lens Dust Cap E
	Magnification with Extension Tube EF12 II	0.17-0.03
	Magnification with Extension Tube EF25 II	0.20-0.07
	Extender Compatibility	Compatible
	Other Accessories	Canon drop-in 52mm filters
Specifications with EF 1.4x II		
	Focal Length	560
	Maximum Aperture	5.6-45
	Maximum Magnification	0.18
	AF Possible	Yes
	IS	Yes
Specifications with EF 2x II		
	Focal Length	800
	Maximum Aperture	8-64
	Maximum Magnification	0.26
	AF Possible	Yes ¹¹
	IS	Yes ¹²

² Minimum aperture if using 1/3stop increments

⁴ Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

³ AF Full Time Manual Focus

¹¹ AF possible with EOS-1 series only and 5D Mark III with firmware 1.2.1

¹² IS will not work with the following cameras EOS-1, EOS 5, EOS 100, EF-M, EOS 1000/F/n/Fn, EOS 700, EOS 10, EOS RT, EOS 600/630, EOS 850, EOS 750, EOS 620, EOS 650

¹³ Lens dimensions when in retracted state

¹⁵ Tested under CIPA standards